



# B SERIES INCLUSIONS

When you build with Burbank, you can rest assured you'll receive the highest quality fittings and finishes as well as outstanding workmanship and exceptional service along the way.



Effective from 1st May 2024

## BUILDING ALLOTMENT

- Building allotment of up to 700m<sup>2</sup> with a maximum building set back of 5m (subject to planning authority)
- All our homes are built to a N2 wind rating which is the wind classification based off the location of your home, shielding, topography and terrain conditions

## NCC 2022

All of our homes are designed and built to meet NCC 2022 requirements. This includes requirements for:

- Liveable Housing
- Condensation Management
- Whole of Home including a minimum 1.5 kilowatt Solar Photovoltaic System and 200L split system heat pump
- 7 Star NatHERS Rating to all orientations<sup>^</sup>

## WARRANTIES & ASSURANCES

- 30 year structural guarantee\*

## SERVICES - CONNECTIONS

- Connection to water, sewer (up to 1500mm deep) and stormwater points within the allotment and connection to underground power and gas services immediately adjacent to the allotment. Excludes internet and telephone connections and associated costs
- 2x external water taps (1x at water meter and 1x to rear of home)
- Three phase power included from front of allotment to meter box up to 10m run

## FOOTINGS

- Engineer designed 'H1' class concrete slab with one concrete pump allowance
- Concrete 'H1' class waffle concrete slab to alfresco and porch where applicable
- Balance cut and fill up to 300mm (with no existing fill) over build platform
- Termite physical barrier to external perimeter and shields to all service penetrations

## CEILING HEIGHTS

- 2590mm ceiling height for single storey homes with a 75mm cove cornice
- 2590mm (nominal) ceiling height to ground floor of double storey homes with 2440mm (nominal) ceiling height to first floor

## WINDOWS

- Aluminum awning windows throughout (including locks), unless otherwise noted on facade selection. Note upper storey bedroom window openings may be restricted to comply with building regulations
- Brick infill above windows (if facade contains lightweight cladding, brick infill won't apply)
- Flyscreens (aluminum mesh) applied to all windows

## ROOFING

- Choice of coloured concrete roof tiles with 22.5 degree roof pitch or Colobond<sup>®</sup> metal roof. Note: Choice dependent on facade and roofline
- Colorbond<sup>®</sup> steel fascia, quad gutter and rectangular downpipes

## EAVES

- 450mm eaves to ground floor facade and first floor as determined by home design and facade type

## EXTERIOR DOORS

- Front entry hinged door including weather seal and entrance lockset with keyed alike deadbolt
- Garage access (if applicable) with flush panel door and lockset (no deadbolt)
- Laundry hinged flush panel door with half light and lockset - no deadbolt (plan specific)

## CAR ACCOMMODATION

- Lock up garage under main roofline
- Motorised (2 x remote) sectional overhead door with painted cement sheet infill
- Rear pedestrian access door (pending space availability)
- Plaster lined ceiling and side walls
- Structural concrete floor at same finished floor level to living areas
- Double power point and batten light point

## BRICKS

- Inclusion bricks with raked or rolled joints including brick sills

## KITCHEN & APPLIANCES

- 20mm engineered stone benchtop with arris edge
- 900mm electric oven with 900mm gas cooktop
- 900mm stainless steel slide out rangehood
- Fully lined laminate base and overhead cupboards with handles
- Metal sided drawer runners (1 x four bank drawer module)
- Pantry with 4x fully lined melamine shelves at 450mm in depth
- Tiled splashback to kitchen including returns
- Kitchen mixer tap
- Double bowl sink with single drainer
- Dishwasher provision
- Microwave provision

## WET AREA FIXTURES

- Shower rose with mixer tap
- 900mm x 900mm tiled shower base with chrome waste
- Semi-framed shower screen with pivot door
- Acrylic bath with wall mounted mixer tap and spout
- Ceramic closed coupled toilet suite
- Ceramic above counter basin with mixer tap
- Laminated vanity. Width of vanity determined from chosen floorplan
- Toilet roll holders
- Towel ring to bathroom, ensuite and powder room
- Mixer tap with inset trough and laminate cabinet to laundry (if size permits)
- 2x stop taps to washing machine (1x hot, 1x cold)
- Frameless mirror to the width of the vanity

## FRAMING

- 90mm prefabricated pine frame and roof trusses

## FIXING

- Internal hinged doors with knob handle
- Doorstops throughout
- Sliding vinyl robe doors with single lined shelf with metal hanging rod
- Joinery - Paint finished MDF 67x12mm skirtings and 42x12mm architraves throughout

## STAIRCASE (IF APPLICABLE)

- MDF treads and risers including plaster dwarf walls to stairs and void areas
- Pine handrail as required for chosen design

## HEATING

- Ducted heating (gas fired and manual thermostat) with ceiling ducts to all habitable rooms (includes bedrooms) in accordance with manufacturer's specification

## PAINT

- Three coat paint system throughout the home
- Low sheen washable acrylic paint to internal walls and ceiling
- Gloss enamel paint to internal timberwork and doors
- Walls and internal woodwork to be 1x colour throughout (white ceilings optional)
- Acrylic paint finish to exterior timber, metal work and cladding, gloss finish to entrance door

## ELECTRICAL

- Batten holder light points with energy efficient globes and shades
- Weatherproof batten fitting to above outside external doors, excluding garage
- Double power points throughout
- RCD safety switch
- TV point
- Telephone point (1x)
- Externally ducted exhaust fans over showers
- Hard wired smoke alarms
- Clipsal Iconic slim white cover plates

## WET AREA TILING

- Floor and wall tiles to wet areas
- Tiles to shower walls with a minimum 2000mm above shower base
- Tiled bath hob with 600mm high splashback above bath
- 100mm tiled skirtings to match floor tiles

\*Conditions apply. 30 year structural guarantee: for full details head to [www.burbank.com.au/victoria/terms-conditions](http://www.burbank.com.au/victoria/terms-conditions). The list of items mentioned herein form part of the items included in the base house price of all Victorian Burbank Home Designs. Any items selected by the customer that are not included in this list will result in additional costs to the contract price. All items are subject to manufacturers/suppliers availability. Burbank (Burbank Australia Pty Ltd) reserves the right to replace or substitute any of the listed items with items of equal or greater value. <sup>^</sup>Based on climate zone 60-Tullamarine with standard floorplan and Riverside façade for double storey homes and Inglewood façade for single storey homes. Excludes house type Cordova 45 with orientation 315 degrees, Keystone 37 with orientation 135, 180 and 225 degrees. As per NatHERS Technical Note, 23 October 2023 - Current, clause 8.8, Burbank have applied a medium solar absorbance value of 0.5 for external colours and master plan internal flooring coverings in determining energy rating value/stars. Please consult your Sales Consultant or [www.burbank.com.au](http://www.burbank.com.au) for further information.

## VICTORIA