



EXTERNAL FEATURES

BRICKS

· Select from Burbank inclusion range

ROOFING

 Select from Burbank inclusion range of concrete roof tiles (colour on) with roof pitch, or as predetermined by façade selection

HOT WATER SERVICE

· Energy efficient heat pump (170lt)

EXTERIOR HINGED DOORS

- Front entry Burbank inclusion range as predetermined with façade choice. Includes weather seal and passage set with keyed alike deadbolt
- Clear glazing to door and sidelight/s (if applicable)
- Garage access (if applicable), with keyed alike entrance set

CAR ACCOMMODATION

- Lock up garage under main roofline, including sectional door with painted cement sheet clad lintel from Burbank inclusion range, or as predetermined with façade options
- · Rear pedestrian access door (space permitting)
- · Plaster lined ceiling and side walls
- · Structural concrete floor
- · Double power point and batten light point

PAINT

 Acrylic paint finish to exterior timber, metal work and cladding, gloss finish to entrance door

ELECTRICAL

Batten light point located near external doors, excluding garage

BUILDING STRUCTURE

BUILDING ALLOTMENT

 Based on building allotment of up to 600m² and a maximum building setback of 6m (subject to planning authority)

FRAMING

 Prefabricated stabilised 90mm pine wall frames and roof trusses

SERVICES - CONNECTIONS

 Includes connection to water, sewer and stormwater points within the allotment and connection to underground power services immediately adjacent to the allotment. Excludes telephone and/or fibre connection costs and all consumer account-opening fees

FOOTINGS

- Concrete engineer designed 'S' class (1 concrete pump allowance)
- Maximum 500mm fall and no existing fill to site with balanced cut and fill (slab costs will be adjusted if founding conditions differ)
- 30 year structural guarantee*
- 75mm visual termite protection to comply with AS3660

INSULATION (DWELLING ONLY)

 Sisalation wrap to all external walls, R2.5 batts to ceiling (excluding garage and alfresco)

PLUMBING

- Concealed plumbing (except for spa pump if applicable), poly piping
- Colorbond® fascia, quad gutter and PVC downpipes

INTERNAL FEATURES

FIXING

- Joinery painted finish MDF 68 x 12mm skirting and 42 x 12mm architraves throughout
- Burbank inclusion range flush panel door 2040mm high
- Internal door furniture selected from Burbank inclusion range

LIGHTING

· Batten holder light points with shades

PAINT

- Two-coat application of Burbank inclusion range paint throughout
- Low sheen washable acrylic paint to internal walls
- · Flat acrylic ceiling paint
- Gloss enamel paint to internal timberwork and doors

Note: walls, ceilings and internal woodwork to be 1 colour throughout (white ceilings optional)

ELECTRICAL

- · RCD safety switch
- · Double power points throughout
- TV point
- · Smoke detectors, wired direct
- White Iconic Range cover plates

CEILING HEIGHTS

- 2440mm ceiling heights with 90mm cove cornice
- 2590mm ground floor, 2440mm upper floor (nominal) for double storey (specific design exceptions may apply)

WINDOWS

 Aluminium sliding throughout (including locks), unless otherwise noted on façade selection.
Upper storey bedroom window openings restricted to comply with building regulations

STAIRCASE (IF APPLICABLE)

 MDF treads and risers including plaster half height walls (going up a staircase) and to void areas

KITCHEN APPLIANCES, CABINETRY & TAPWARE

OVEN

• 600mm electric stainless steel

RANGEHOOD

 900mm stainless steel recirculating canopy (not including charcoal filters)

СООКТОР

• 900mm ceramic glass top electric cooktop

SINK AND MIXER

- Flick mixer tap to sink
- Long double bowl sink

MICROWAVE

Microwave space with pot drawer and power point

PANTRY

· Pantry with 4 melamine shelves

ELECTRICAL

· Telephone point to kitchen

CUPBOARDS

· Base cupboards with melamine shelving

DISHWASHER

· Dishwasher space and connections

DENCUTOR

 Burbank inclusion range laminated bench tops and pre-laminated doors and panels

ROBES

 Single melamine shelf with metal hanging rod and full height sliding doors

LINEN

· Four melamine shelves

BATHROOM, ENSUITE & LAUNDRY

SHOWER TILES

- · Shower tiles to minimum 2000mm above base
- · Tiled shower base
- Bath tiles to hob and minimum 600mm above base

SHOWER SCREEN

 Burbank inclusion range framed pivot shower screen to 1950mm high

SHOWER/BATH

- 9lt per minute shower rose on all directional arm with mixer tap
- Acrylic bath with mixer tap

VANITY

- Burbank inclusion range laminated vanity (width nominated by plans)
- Inset china round basin and mixer tap with pin handle

FAN

· Exhaust fans over showers

TOILET

Vitreous china closed coupled soft close toilet seat

LAUNDRY

- Flick mixer tap with 45lt stainless steel trough
- · 600mm metal laundry cabinet
- 2 x stop taps to washing machine (1 hot and 1 cold)

FLOORING

- Burbank inclusion range ceramic tiles to wet areas as noted on plan
- Half height tiled skirting to tiled areas (200mm maximum)

The inclusions stated herein are included in all Burbank (QLD) Collection home products. Any items not included in this inclusions brochure selected by the purchaser will attract additional costs. Burbank Australia (QLD) Pty Ltd ('Burbank') reserves the right to vary or omit any items listed herein. All items are subject to availability. Conditions apply for Burbank's 30 year structural guarantee, see website for full details.

Queensland Office Unit 11, 1-15 Lexington Road, Underwood, Queensland Burbank Australia (QLD) Pty Ltd ABN 77 103 014 615 QBCC 1046544