B

Premium Inclusions



When you build with Burbank, you can rest assured you'll receive the highest quality fittings and finishes as well as outstanding workmanship and exceptional service along the way.

Effective from 4th August 2025

BUILDING ALLOTMENT

- Building allotment of up to 700m2 with a maximum building set back of 5m (subject to planning authority)
- All our homes are built to a N2 wind rating. Wind classifications are based off the location of your home, shielding, topography and terrain conditions

NCC 2022

All of our homes are designed and built to meet NCC 2022 requirements. This includes requirements for:

- Livable Housing
- · Condensation Management
- Minimum 1.5 kilowatt Solar Photovoltaic System and minimum of 280L (house specific) for double storeys, minimum of 205L (house specific) for single storeys electric boosted heat pump hot water system
- 7 Star NatHERS Rating to all orientations[^]

WARRANTIES & ASSURANCES

30 year structural guarantee*

SERVICES - CONNECTIONS

- Connection to water, sewer (up to 1500mm deep) and stormwater points within the allotment and connection to underground power and gas services immediately adjacent to the allotment (up to 10m and excluding service provider fees). Excludes internet and telephone connections and associated costs
- 2x external water taps (1x at water meter and 1x to rear of home)
- Three phase power included from front of allotment to meter box up to 10m run

FOOTINGS

- Engineer designed 'H1' class concrete slab with one concrete pump allowance
- Concrete 'H1' class waffle concrete slab to alfresco and porch where applicable
- Balance cut and fill up to 300mm (with no existing fill) over build platform
- Termite physical barrier to external perimeter and shields to all service penetrations

CEILING HEIGHTS

- 2590mm ceiling height for single storey homes with a 75mm cove cornice
- 2590mm (nominal) ceiling height to ground floor of double storey homes with 2440mm (nominal) ceiling height to first floor

BRICKS

Inclusion bricks with raked or rolled joints including brick sills

WINDOWS

- Aluminum awning windows throughout (including locks), unless otherwise noted on facade selection. Note upper storey bedroom window openings may be restricted to comply with building regulations
- Brick infill above windows (if facade contains lightweight cladding, brick infill won't apply)
- Flyscreens (fibreglass mesh) applied to all windows

ROOFING

- Choice of coloured concrete roof tiles with 22.5 degree roof pitch
- Colorbond® steel fascia, quad gutter and rectangular downpipes

EAVES

 450mm eaves to ground floor facade and first floor as determined by home design and facade type

EXTERIOR DOORS

- Front entry clear glazed timber hinged door including weather seal and entrance lockset with keyed alike deadbolt
- Garage access (if applicable) with flush panel door, weather seal and lockset (no deadbolt)
- Laundry hinged flush panel door with half light and lockset no deadbolt (plan specific)

CAR ACCOMMODATION

- Motorised sectional garage door
 (2x handset remotes and 1x wall remote)
- Rear pedestrian access door (pending space availability)
- Plaster lined ceiling and side walls
- Structural concrete floor at same finished floor level to living areas
- Double power point and batten light point

KITCHEN & APPLIANCES

- 20mm Stone Ambassador benchtop (Zenith inclusion range)
- 900mm electric oven with 900mm gas cooktop
- 900mm stainless steel slide out rangehood
- Fully lined laminate base and overhead cupboards with handles
- Metal sided drawer runners (1 x four bank drawer module)
- Pantry with 4x fully lined melamine shelves at 450mm in depth
- Tiled splashback to kitchen including returns
- Kitchen mixer tap
- Double bowl sink with single drainer
- Dishwasher provision
- Microwave provision

T 13 2872 | **E** enquiries@burbank.com.au | **W** burbank.com.au



Premium Inclusions



When you build with Burbank, you can rest assured you'll receive the highest quality fittings and finishes as well as outstanding workmanship and exceptional service along the way.

Effective from 4th August 2025

WET AREA FIXTURES

- Shower on rail with mixer tap
- 900mm x 900mm tiled shower base with chrome waste
- · Semi-framed shower screen
- Acrylic bath with wall mounted mixer tap and spout
- · Ceramic closed coupled toilet suite
- Ceramic above counter basin with mixer tap
- Wall hung laminate vanity. Width of vanity determined from chosen floorplan
- Toilet roll holders
- · Towel rail to bathroom and ensuite, towel ring to powder room
- Mixer tap with inset trough and laminate cabinet to laundry (if size permits)
- 2x stop taps to washing machine (1x hot, 1x cold)
- Frameless mirror to the width of the vanity

FRAMING

90mm prefabricated pine frame and roof trusses

FIXING

- Internal hinged doors withlever handle (including privacy locks to all bathrooms)
- · Doorstops throughout
- Sliding robe doors with single lined shelf with metal hanging rod
- Joinery Paint finished MDF 67x18mm skirtings and 67x18mm architraves throughout

STAIRCASE (IF APPLICABLE)

- MDF treads and risers including plaster dwarf walls to stairs and void areas
- Pine handrail as required for chosen design

HEATING

 Ducted heating (gas fired and manual thermostat) with ceiling ducts to all habitable rooms (includes bedrooms) in accordance with manufacturer's specification

PAINT

- Three coat paint system throughout the home
- Low sheen acrylic paint to internal walls and ceiling
- · Water based gloss enamel paint to internal timberwork and doors
- Walls and internal woodwork to be 1x colour throughout (white ceilings optional)
- Acrylic paint finish to exterior timber, metal work and cladding, gloss finish to entrance door

ELECTRICAL

- Batten holder light points with energy efficient globes and shades
- Weatherproof batten fitting to above outside external doors, excluding garage
- Double power points throughout
- RCD safety switch
- TV point
- Telephone point (1x)
- · Externally ducted exhaust fans over showers
- · Hard wired smoke alarms
- Clipsal Iconic slim white cover plates

WET AREA TILING

- Floor and wall tiles to wet areas
- Tiles to shower walls with a minimum 2000mm above shower base
- Tiled bath hob with 600mm high splashback above bath
- 100mm tiled skirtings to match floor tiles

T 13 2872 | **E** enquiries@burbank.com.au | **W** burbank.com.au