Premium Inclusions

△ Burbank

When you build with Burbank, you can rest assured you'll receive the highest quality fittings and finishes as well as outstanding workmanship and exceptional service along the way.

Effective from 4th August 2025

BUILDING ALLOTMENT

- Building allotment of up to 600m2 with a maximum building set back of 6m (subject to planning authority)
- All our homes are built to a N2 wind rating. Wind classifications are based off the location of your home, shielding, topography and terrain conditions.

NCC 2022

All of our homes are designed and built to meet NCC 2022 requirements. This includes requirements for:

- Livable Housing
- Minimum 280L (house specific) electric boosted heat pump hot water system to double storeys, minimum of 205L (house specific) for single storeys
- 7 Star NatHERS Rating to all orientations[^]
- Ceiling fans (with lights) to all habitable rooms

WARRANTIES & ASSURANCES

30 year structural guarantee*

SERVICES - CONNECTIONS

- Connection to water, sewer and stormwater points within the allotment and connection to underground power services immediately adjacent to the allotment (up to 10m and excluding service provider fees). Excludes internet and telephone connections and associated costs
- 2x external water taps (1x at front and 1x at rear)
- Three phase power connection including multi-circuit board (if electricity capacity exists)

FOOTINGS

- Engineer designed 'M' class concrete slab including porch and alfresco as per nominated floorplan with one concrete pump allowance
- Balance cut and fill up to 500mm (with no existing fill) over build platform
- Physical termite treatment system to slab perimeter and shield to all service penetrations.

COUNCIL FEES & REQUIREMENTS

- QBCC levies & insurances
- Approval fees paid including sewage plan, design flood level, building development approval, plumbing & energy reports (based on Brisbane City Council)

CEILING HEIGHTS

- 2440mm (nominal and facade specific) ceiling height
- 2590mm (nominal) ceiling height to ground floor of double storey homes with 2440mm (nominal) ceiling height to first floor
- 90mm cove cornice

FRAMING

90mm termite treated prefabricated pine frame and roof trusses

WINDOWS

- Aluminium sliding throughout (including locks), unless otherwise noted on facade selection. Note upper storey bedroom window openings may be restricted to comply with building regulations
- Brick infill above windows and doors with steel lintels to front of single storey (facade specific). Brick i
- nfill to ground floor of double storey (facade specific).
- Lightweight cladding infill above all other windows and doors to ground and first floors.

ROOFING

- Choice of coloured concrete roof tiles with 22.5 degree roof pitch or Colorbond® metal roof.
 - Note: Choice dependent on facade and roofline
- Colorbond® steel fascia, quad gutter and round PVC downpipes

EAVES

 450mm eaves to single and double storey homes as determined by home design and facade type

EXTERIOR HINGED DOORS

- Front entry clear glazed timber hinged door including weather seal and entrance lockset with keyed alike deadbolt
- Garage access (if applicable) with flush panel door, weather seal and lockset (no deadbolt)

BRICKS

· Inclusion bricks with raked or rolled joints including brick sills

CAR ACCOMMODATION

- Motorised sectional garage door
 (2x handset remotes and 1x wall remote)
- Sectional overhead door with painted cement sheet infill
- Rear pedestrian access door (pending space availability)
- Plaster lined ceiling and side walls
- Structural concrete floor
- · Double power point and batten light point

T 13 2872 | **E** qld.enquiries@burbank.com.au | **W** burbank.com.au

QUEENSLAND

Burbank Australia Pty Ltd | Unit 11/1-15 Lexington Road, Underwood 4119 | ABN 77 103 014 615 | QBCC 1046544

Premium Inclusions



When you build with Burbank, you can rest assured you'll receive the highest quality fittings and finishes as well as outstanding workmanship and exceptional service along the way.

Effective from 1st July 2025

KITCHEN & APPLIANCES

- Inclusion range laminated benchtop
- 900mm electric oven with 900mm induction cooktop
- 900mm externally ducted rangehood and overhead cupboard to suit
- Fully lined laminate base and overhead cupboard with handles
- Metal sided drawer runners (1x four bank drawer module)
- Pantry with 4x fully lined melamine shelves at 450mm in width
- Tiled splashback to kitchen including returns
- Kitchen mixer tap
- Double bowl sink with single drainer
- Dishwasher provision
- Microwave provision

WET AREA FIXTURES

- Mixer tap with inset trough and laminate cabinet to laundry (if size permits)
- Shower on rail with mixer tap
- 900mm x 900mm tiled shower base
- Pivot softline semi-framed shower screen
- Acrylic bath with wall mounted mixer tap and spout
- · Ceramic closed coupled toilet suite
- · Ceramic above counter basin with mixer tap
- Wall hung laminate vanity. Width of vanity determined from chosen floorplan
- Toilet roll holders
- Towel rail to bathroom and ensuite, towel ring to powder room
- 2x stop taps to washing machine (1x hot, 1x cold)
- · Frameless mirror to the width of the vanity

FIXING

- Corinthian internal hinged doors with lever handle (including privacy locks to all bathrooms)
- Doorstops throughout
- · Sliding robe doors with single lined shelf with metal hanging rod
- Joinery Paint finished MDF 67x18mm skirtings and 67x18mm architraves throughout

STAIRCASE (IF APPLICABLE)

- MDF treads and risers including plaster dwarf walls to stairs and void areas
- Pine handrail as required for chosen design

PAINT

- · Three coat Taubmans paint system throughout the home
- Low sheen acrylic paint to internal walls and ceiling
- Water based gloss enamel paint to internal timberwork and doors
- Walls and internal woodwork to be 1x colour throughout (white ceilings optional)
- Acrylic paint finish to exterior timber, metal work and cladding, gloss finish to entrance door

ELECTRICAL

- · Batten holder light points with energy efficient globes and shades
- Weatherproof batten fitting to outside external doors, excluding garage
- Double power points throughout
- · RCD safety switch
- TV point
- Telephone point (1x)
- Externally ducted exhaust fans over showers
- Hard wired smoke alarms
- · Clipsal Iconic slim range slim white cover plates

WET AREA TILING

- Floor and wall tiles to wet areas.
- · Tiles to shower walls with a minimum 2000mm above shower base
- Tiled bath hob with 600mm high splashback above bath
- 100mm tiled skirtings to match floor tiles

T 13 2872 | **E** qld.enquiries@burbank.com.au | **W** burbank.com.au